



GT Wire Rope Pulling Hoist

The GT Wire Rope Pulling machine is an extremely versatile and portable unit for pulling, lifting, lowering and securing loads, that is both easy and safe to operate.

- All machines are supplied complete with 20 metre wire rope and an extendable operating lever.
- Wire rope is tapered one end and fitted with a hook and safety catch at the other end.
- Only the GT specially manufactured wire rope supplied will ensure correct functioning.
- The machine has low maintenance requirements and is easy to service.
- Overload protection ensures high personal safety when in operation.

lifting capacity (kgs)	pulling capacity (kgs)	rope diameter (mm)	overall length of body (mm)	overall width of body (mm)	overall height of body (mm)	weight nett (kgs)
800	1250	8.3	426	64	235	6
1600	2500	11	545	97	280	11
3200	5000	16	660	116	325	22



GT Pallet Truck

The GT pallet trucks, with capacities up to 3500 kgs are efficient, economic and easy to operate. Their heavy duty hydraulic pumps enable continuous and reliable use in the most difficult of conditions.

- Standard production is supplied with nylon wheels for extra reliability.
- Individually tested and supplied with proof load certificates.
- Load and steering wheels can be supplied in polyurethane or rubber.
- Specially tapered fork tips.
- Three position control handle.

capacity (kgs)	load rollers	min. lowered fork height (mm)	width over forks (mm)	fork length (mm)	fork width (mm)	weight nett (kgs)
2500	Double Nylon	75	550	1000	160	71
2500	Double Nylon	75	550	1100	160	78
2500	Double Nylon	75	685	1220	160	95
3000	Double Nylon	75	550	1100	160	78
3500	Double Nylon	75	550	1100	160	78

NEVER EXCEED MAXIMUM CAPACITY

George Taylor & Co. also offer low temperature, high lift and stainless steel manual pallet trucks



George Taylor & Company Lifting Gear (Midlands) Ltd. Brickyard Road, Aldridge, West Midlands WS9 8SR

Telephone: 01922 457916 or visit: www.gtlifting.co.uk

ALL OFFERS ARE SUBJECT TO OUR CONDITIONS OF BUSINESS