

KRATOS - EVACUATION TRIANGLE INSTRUCTIONS



For your safety, comply strictly with the instructions for use, verification, maintenance and storage. George Taylor & Co. cannot be held liable for any direct or indirect accident occurring as a result of use other than provided for in this notice; do not use this equipment beyond its capabilities!

USE & PRECAUTIONS

A evacuation triangle is intended to be used to rescue a conscious person (adult) and allow it to be removed up or down through the intervention of other people. The evacuation triangle can be used by one person at a time. Place the triangle on the user and collect the three attachment points in the following sense: attaching side - central end - attaching side, and pass a connector (EN 362) in these attachments. During these operations ensure that the straps do not twist.



Make sure, that the injured person is correctly positioned to allow the rescue operations.

For safety reasons and before each use, make sure that there is no obstacle obstructing the normal deployment of the rescue system.

Rescue operations require, most of time, to make emergency intervention, so it is important that those involved are firstly formed and trained in this kind of intervention.

The anchorage point of the rescue system should be strong enough, minimum strength: 15 kN, (EN 795).

Ensure that rescue operations limit the pendulum effect, the risk and the height of a fall. This equipment is suitable for use on site in the open air and a temperature range of -40°C à $+60^{\circ}\text{C}$.

This equipment is for the sole use of people trained, skilled and in good health, or under the supervision of a trained and skilled person.

Warning! Certain medical conditions may affect user safety, if in doubt, consult your doctor.

Sharp edges, small diameter structures and corrosion should be avoided as they may affect the performance of the webbings.

Check the condition of the rescue triangle before every use: visual inspection to check the condition of the straps (no signs of cuts, burns or abnormal shrinkage), the seams (no visible damage), the metal parts (no deformation or rust) and that the connectors work properly. In the event of deformation or doubt the equipment should not be reused. Do not remove, add or replace any component of the equipment.

TECHNICAL CHARACTERISTICS

Belt material: polyester and/or polyamide. Buckle material: heat treated steel.

SUITABILITY FOR USE

The triangle must be used as part of a rescue system: EN341 ; EN1496.... It may be dangerous to create one's own rescue system where each safety function can interfere with another safety function. Read the recommendations on using each component in the system before use.

VERIFICATION PROCEDURE

The equipment has a service life of 5 years, but this may increase or decrease depending on how it is used and/or the results of annual checks. The equipment must be checked systematically in case of doubt or after a fall and at least every year by the manufacturer or his authorised representative, to guarantee its state and thus the safety of the end-user. The product data sheet should be completed after each annual verification.

SERVICING AND STORAGE

(Comply strictly with these instructions)

During transport, keep the equipment in its packaging, well away from any cutting surface. Clean it with water and soap, wipe it with a dry rag and hang it up in a well-ventilated location, to let it dry naturally and away from a naked flame or heat source; follow the same procedure for components that have become damp during use. The metal parts should be wiped with a cloth impregnated with paraffin oil. Never use bleach or detergents. The equipment should be stored in its packaging in a warm, dry, ventilated place, protected from sunlight, heat and chemicals.